

# New Capricorn Pump Set Oil

## Product Description:

New Capricorn Pump Set Oil is blended from highly refined HVI base stocks and a combination of anti-oxidant, anti-wear and anti-foam additives.

## Applications:

- ¾ Lubrication of bearings and cylinders of diesel engines where operating conditions require high detergency type engine oil.
- ¾ Ideal for slow, medium and high speed stationary diesel engines equipped on agricultural pump house.

## Features:

- ¾ Clean engine with lesser deposits and good anti-oxidant, anti-wear and anti-weld properties.

## Specification Level:

- ¾ Meets MIL-L-2104C and API SE/CD
- ¾ Meets E-PL 2 and E-DL 2 of BIS 13656-1993.

## Typical Characteristics:

S.No.	Test	UOM	Test Method	Specification of Pump Set Oil (Agri.)	
				SAE-30	SAE-40
1	Appearance & Clarity	NA	Visual	Bright & Clear Fluid	
3	Density @ 29.5°C	gms/cc	ASTM D 1298	0.876-0.885	0.8800-0.888
4	Kin. Viscosity @ 100°C	CSt.	ASTM D 445 /IP 71	10.5 to 12.5	13.5 to 15.8
5	Kin. Viscosity @ 40°C	CSt.	ASTM D 445 / IP 71	To record	
6	Viscosity Index	NA	ASTM D 2270/ IP 226	+95 (Min.)	+90 (Min.)
7	Total Base No. (Min)	mg.KOH/ gm.	ASTM D 2296	10.00	10.00
8	Flash Point (COC)	°C	ASTM D 92	220	225
9	Pour Point (Min)	°C	ASTM D 97/ IP 15	-6	-6
10	% Sulphated Ash	Mass	ASTM D 874	1.7 (Max.)	1.7 (Max.)

NA implies "NOT APPLICABLE".

The values mentioned above are subject to change due to our continued R & D.

**Packs Sold:-** The above product is available in 210 Ltrs. Barrel and 20 Ltrs. Plastic Pail / Mini-drum.